

**REPORT DOCUMENTATION PAGE**Form Approved  
OMB NO. 0704-0188

Public Reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comment regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave Blank)		2. REPORT DATE February 12, 2003	3. REPORT TYPE AND DATES COVERED Final Progress Report, 15 Jul 02 - 14 Jan 03
4. TITLE AND SUBTITLE  Sample Concentration Systems for Fast Laboratory Evaluation of Sensory Materials for Chemical and Biological Agent Detection in Water		5. FUNDING NUMBERS G - DAAD19-02-1-0301	
6. AUTHOR(S) Jian-Qiao Sun			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)  University of Delaware, Department of Mechanical Engineering 126 Spencer Lab Newark, DE 19716		8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)  U. S. Army Research Office P.O. Box 12211 Research Triangle Park, NC 27709-2211		10. SPONSORING / MONITORING AGENCY REPORT NUMBER  44038.1 - CH-11	
11. SUPPLEMENTARY NOTES The views, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy or decision, unless so designated by other documentation.			
12 a. DISTRIBUTION / AVAILABILITY STATEMENT  Approved for public release; distribution unlimited.		12 b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  This report summarizes the prototyping work of micro pumps with micro fluid channels for fast material evaluation of sensory materials for chemical and biological agent detection. The work conducted under this project is a six-month pilot study. The objective of the research is to help speed up the C&B sensory material research at the Army Research Laboratory in Aberdeen, Maryland. Several prototypes of the micro pumps with different fluid channels have been studied. Experiments of sample concentration with the micro pump test station have been conducted in the ARL, and demonstrated significant improvement of the response of the sensory material to various chemical agents.			
14. SUBJECT TERMS  Micro pumps, surface machining, miniaturization, sample concentration, C&B sensors		15. NUMBER OF PAGES 3	
		16. PRICE CODE	
17. SECURITY CLASSIFICATION OR REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION ON THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT  UL

20030317 121

---

**REPORT DOCUMENTATION PAGE (SF298)**  
**(Continuation Sheet)**

---

**Statement of the Work**

The work conducted under this project is a six-month pilot study. The objective of the research is to help speed up the C&B sensory material research at the Army Research Laboratory in Aberdeen, Maryland. Several prototypes of the micro pumps with different fluid channels have been studied. Experiments of sample concentration with the micro pump test station have been conducted in the ARL, and demonstrated significant improvement of the response of the sensory material to various chemical agents. In the meantime, we have also demonstrated the feasibility of concept micro pumps fabricated by the surface machining technology. The surface machining technology is the basic operation of semi-conductor industry, and has a potential to make miniature pumps that can be readily integrated with the electronic control circuitry.

**Summary of the Results**

This project is a continuation of an earlier effort to develop micro pumps for sample concentration. During this project period, we have made several prototypes of micro pumps, and have evaluated the effectiveness of sample concentration at the Army Research Laboratory in Aberdeen, Maryland.




Figure 1. Desk micro pump station with sample concentration mechanism and fluid channels. The cylinder on the top of the platform is the reservoir of the chemical solution.

We made several micro pump stations with a reservoir for containing and recycling the chemical solution. The surface machining technology was used in fabrication of the systems. Power supply units have also been made in connection to the stations. A prototype pump is shown Figure 1. The fluid is pumped through a small channel in a plexiglass body, where the sample ticks coated with the C&B detecting materials developed by the researchers of ARL at Aberdeen. Three undergraduate students in the Department of Mechanical Engineering have been working on this project.

One of the micro pumps is driven by a linear solenoid powered by a PWM voltage source. The shaft of the solenoid is attached to the diaphragm, which pumps the fluid. A schematic of the micro pump is shown in Figure 2. The whole system is confined in a  $2.5 \times 6.3 \times 10 \text{ cm}^3$  rectangular body. This choice of the dimensions was made with a consideration of a possible pocket size implementation of the chemical and biological sensors.




Figure 2. A schematic drawing of the micro pump with a linear solenoid motor.

Experiments of sample concentration with the micro pump test station have been conducted in the ARL, and demonstrated significant improvement of the response of the sensory material to various chemical agents. Figure 3 shows some results of optical reading of the C&B detection material after being exposed to the chemical agent for a fixed period of time. Since the flow over the surface of the test ticket as shown in Figure 4 is turbulent by way of the design of the fluid channel, the C&B detection material has a much higher exposure to the chemical agent, and thus has shown a significantly higher response as shown in the figure.




Figure 3. With 100% concentration of the chemical, the ARL researcher obtained the optical intensity reading between 600 and 700. With the solution diluted by 25 times, pump 3 with an improved fluid channel gives a maximum intensity reading 148. This represents a significant improvement of sensitivity by means of the sample concentration mechanism.




Figure 4. The ticket coated with the C&B detection material.

The work done in the past six months has helped the researchers of ARL at Aberdeen to speed up the R&D of C&B detection materials. The effort of this project can be extended to study the effectiveness of large-scale sample concentration systems for C&B detection in the water supply.

**List of Participating Scientific Personnel**

Professor J.Q. Sun, Mechanical Engineering, University of Delaware

Todd M. Fitzgerald, junior undergraduate student, BS 2004, Mechanical Engineering, University of Delaware

Kirstin Huesmann, senior undergraduate student, BS 2003, Mechanical Engineering, University of Delaware

Silvia Pineda, senior undergraduate student, BS 2003, Mechanical Engineering, University of Delaware